

GRUNT

PH 03 8781 0520 WEB: WW.GRUNT4X4.COM.AU

PART NUMBER: GTG-NP3002



WARNING:
APPLICATION OF SELF ADHESIVE SEAL
The surface must be free from dirt, dust, oil & moisture.
Surface temperature should be approximately 20°C -30°C.
Use of a heat gun is recommended.
Cleaning before application of Grunt 4x4 seal kits is to be done using a supplied cleaner. For extremely dirty surfaces please use Prep wash / Prep sol / Isopropyl Alcohol etc.
Once clean and surface is warm, apply 3M Primer 94 to area where seal is being installed.

Only peel and release 200mm - 300mm at a time to prevent the adhesive picking up foreign material.
The sponge seal is self adhesive and for best results excite the glue before applying by placing into direct sunlight or heating gently with a heat gun or hair dryer.
After fitting seal, leave tailgate close for 24 hours to cure.

Adhesive should be placed on firmly and uniformly 200mm at a time.
DO NOT STRETCH THE SEAL WHEN APPLYING AS IT WILL COME OFF OVER TIME

1: Place self adhesive foam pads in each of the bottom corners of the tub as pictured.

2: Install the lower seal in the indentation running across the bottom of the tub butting up to the pad as shown. make sure you press the seal firmly into the groove.

3: Install the pinchweld seal over the metal edge of the tub. The rubber seal should face the rear of the vehicle

